

VERDER VERDERFLEX®

VERDERFLEX VF80
Technical Data Sheet

Performance Curve




Shimming Curve



VERDERFLEX VF80
Technical Data Sheet

VERDERFLEX®

General Arrangement Layout



All dimensions are in inches.

All dimensions and weights are for guidance only, for construction installation and floor mounting drawings please contact your local authorised Verderflex® distributor.

Standard Materials of Construction

Description	Material	Weight (lbs)	Paint Detail
Pump Housing	Cast Iron (GG25)	1,181	RAL 6018 (Green)
Front Cover	Mild Steel (BS EN10.025:1993/5275)	110	RAL 7021 (Black)
Rotor	Cast Iron (GG25)	198	
Rotor Shoes	Aluminium (6082T6)	33	
Flanges	Universal Slotted 304 Stainless Steel)	27 e.a	
Inserts	Stainless Steel (316L) Polypropylene P.V.D.F	2.2	
Base Frame	Powder Coated Carbon Steel	145	RAL 7035 (Grey)
Lubricant	Verderlube - Glycerine based compound Verdersil - Silicone oil	10.5 gallons	
Hose	NR, NBR, NBR food grade, CSM and EPDM	48	

Close coupled pump unit - "Flat Pack"	1,874

VERDERFLEX
Unit 3, California Drive,
Castleford WF10 5QH
United Kingdom

TEL +44 (0)1924 221 020
FAX +44 (0)113 222 0291
MAIL info@verderflex.com
WEB www.verderflex.com

AT Wien **BE** Aartselaar **BG** Sofia **CH** Basel **CN** Shanghai **CZ** Praha **DE** Haan **FR** Eragny s/Oise **GB** Castleford **HU** Budapest **IT** Torre Boldone **JP** Tokyo **NL** Groningen/Vleuten **PL** Katowice **RO** Bucuresti/Sibiu **RU** St Petersburg **SK** Bratislava **US** Newtown/Macon **ZA** Northriding